

RING-O-MATIC

275



275 STANDARD EQUIPMENT

Enclosed CAT 36 HP Liquid Cooled Diesel Engine
Curbside Control Panel
450 CFM Direct Drive Lobe Type Blower
Large Silencer, Blower Muffler for Noise Abatement of Vacuum Pump
3" Four Position Cast Iron Vacuum-Pressure Valve
2" Pressure Relief Valve
Cat High Pressure Water Pump w/Electric Clutch—5.5 GPM @ 3,200 PSI
Low Water— Pump Shut-Off Switch
1" Fresh Water Filter with 40# Mesh Screen
Cat Pressure Sensitive Regulating Unloader Valve
10 Gal. Fuel Tank
100 Gal. Fresh Water Tank with 1½" Drain Valve
250 Gal. Spoils Tank
Hydraulic Full Opening Rear Door
Door Closure Cammed for Using Single Handle, Moving 4 Deadbolts into Lock Position
Hydraulic Hoist w/Pump, Valve and Steel Reservoir
6" Full Spoils Tank Check Valve
1— 6000# Torlex Rubber Torsion Axle
2— ST235/80 R16 Load Range E Tires
12 Volt Battery
5 Micron Washable Bag Filtration, Wet or Dry Vacuum Capability
3" Drain Valve

1— 2½" Vacuum Relief Valve
1— 2½" Stainless Steel Vacuum Gauge
1— 2½" Stainless Steel Pressure Gauge
25' – 3" Suction Hose
Lockable Hose Reel w/50' HP Hose & Flexible Spray Wand with Nozzle Protector
Patented 3" Stainless Steel Emulsifier w/Rotary Laser Turbo Nozzle – 5'
16" Lawn Sweep on 3" Steel Tube
Pintel Hitch
Optional Strobe & Dual Halogen Work Light Kit (*Shown*)
Optional Anti-Siphon Kit

TONGUE WEIGHTS

Unit Empty: 680#
Full 100 Gal. Water Tank: 740#
Total Dry Weight: 2,740#

DIMENSIONS

Height: 78"
Length: 14'
Width: 63"
GVWR: 6,000#