

RING-O-MATIC

750 DEEP VAC



750 DEEP VAC STANDARD EQUIPMENT

- 20 HP Honda Gas Engine
- 230 CFM Masport Rotary Vein Pump
with 20" Hg Continuous/ 27" Hg Intermittent
- 10 Gal. Fuel Tank
- 750 Gal. Spoils Tank
- 6" Full Spoils Tank Check Valve w/ Rubber Seat
- Pneumatic Breaker In Spoils Tank
- Hydraulic Full Opening Door w/ Pressurized Discharge
- 2 - 6,000# Torflex Rubber Torsion Axles
- 4 - ST235/80 R16 Load Range E Tires
- 12 Volt Battery
- Twin Cylinder Hydraulic Hoist w/ Pump, Valve & Steel Reservoir
- Primary Filter
- 5 Micron Washable Wet or Dry Vacuum Filtration
- 2 1/2" Vacuum Relief Valve
- 1 - 2 1/2" Stainless Steel Vacuum Gauge
- 25' 3" Suction Hose
- 5' Vacuum Tube
- 16" Lawn Sweep
- 50' of 3" Hose Carrying Capacity on Machine
- Pintel Hitch

FOR MORE INFORMATION, contact **Karl Roozeboom** at **641-780-0737** or log on to **www.ring-o-matic.com**