



750

HI CFM PTHD



750 HI CFM PTHD STANDARD EQUIPMENT

Cat 50 HP Diesel Engine w/ Sound Deadening Enclosure
 Curbside Engine Control Panel w/ 2 Electric Shut Down Switches
 850 CFM Lobe Type Blower
 Large Silencer Muffler for Noise Abatement of Vacuum Pump
 Cat High Pressure Water Pump w/ Electric Clutch- 5.5 GPM @ 3500 PSI
 Cat Pressure Sensitive Regulating Unloader Valve
 Low Water—Pump Shut-Off Switch
 1" Fresh Water Filter w/ #40 Mesh Screen
 500 Gal. Total Fresh Water Tanks w/ 1 1/2" Drain Valve
 750 Gal. Steel Spoils Tank w/ 1 1/2" "D" Type Door Seal
 8" Full Spoils Tank Check Valve w/ Rubber Seat
 4" Four Position Cast Iron Vacuum-Pressure Valve
 Pneumatic Breaker in Spoils Tank
 5 Micron Washable Bag Filter w/ 82 Sq. Ft. Filtration, Wet or Dry Vacuum Capability, 3" Drain Valve
 29 Gal. Steel Diesel Tank
 8 Gal. Anti-Freeze Tank w/ 1" PVC 3-Way Valve for Winterization
 Hydraulic Full Opening Rear Door
 Door Closure Cammed for Using Single Handle, Moving 6 Dead Bolts into Lock Position
 Hydraulic Door Cylinder Internally Ported for Safety in the Event of Hose Failure
 Two Cylinder Hydraulic Hoist w/ Pump, Valve & Steel Reservoir
 Two- 2 1/2" Vacuum Relief Valves
 Two- 2 1/2" Stainless Steel Vacuum & Water Gauges

3" Pressure Relief Valve
 Two- 10,000# Torflex Rubber Torsion Axels
 Four- 235/75 R17.5 Load Range H Tires
 Hose Reel w/ 50' of 1/4" HP Hose & Flexible Spray Wand with Nozzle Protector
 Two- 25' X 3" Suction Hoses w/ Ball and Socket Ends
 16" Lawn Sweep on 3" Steel Tube
 Patented 3" Stainless Steel Emulsifier w/ Rotary Turbo Nozzle- 5' Pintel Hitch
 12-Volt Battery

OPTIONAL EQUIPMENT

Pressurized Discharge
 Remote Auxiliary Hydraulic Hookups
 Hose Reel with 100' or 150' of 1/4" HP Hose & Flexible Spray Wand
 Strobe Light & Dual Halogen Work Light Kit- Shown
 8' & 10'- 3" Stainless Steel Emulsifier Guns
 6', 8', & 10'- 3" Stainless Steel Valve Box Clean Out Tools
 6', 8', & 10'-3" Steel Vacuum Tubes Only

DIMENSIONS

Height: 91" Width: 96" Length: 19'-2"