

RING-O-MATIC

VL75



VL75 STANDARD EQUIPMENT

31 HP V-Twin Gas Engine
450 CFM Lobe Type Blower @ 14" Hg. Continuous With Simultaneous 4.7 GPM @ 3400 PSI Water Flow - Giant High Pressure Water Pump
Suttner Pressure Sensitive Regulating Unloader Valve
Large Silencer Muffler for Noise Abatement -80 db
10 Gal. Gas Tank
750 Gal. Spoils Tank
2 -250 Gal. Fresh Water Tanks w/ 1 1/2" Drain Valve
5 Gal. Anti-Freeze Tank w/ 1" PVC 3-Way Valve
Low Water Automatic Engine Shut-off
6" Full Spoils Tank Check Valve w/ Rubber Seat
Hydraulic Full Opening Rear Door
Door Closure Cammed for using a Single Handle, Moving 6 Deadbolts into Lock Position
5 Micron Washable Bag Filtration, Wet or Dry Vacuum Capability, w/ 3" Drain Cap
2 -10,000# Torflex Rubber Torsion Axles
4 - 235/75 R17.5 Load Range H Tires
Twin Cylinder Hydraulic Hoist w/ Pump, Valve & Steel Reservoir
1 - 2" Vacuum Relief Valve

Lockable Hose Reel w/ 50' HP Hose & Flexible Spray Wand with Nozzle Protector
Patented 3" Steel Emulsifier Gun w/Rotary Laser Turbo Nozzle - 5'
16" Lawn Sweep On 3" Steel Tube
1 - 2 1/2" Stainless Steel Vacuum Gauge
33' x 3" Suction Hose
12 Volt Battery
Pintel Hitch

NOTES

Always Under 1,000# Tongue Weight

DIMENSIONS

Height: 84" Width: 96" Length: 19'2"